



## 2 Port KVM Switch With Built-in Cables: KVM-C102U/C102UA/C102P/C102PA

Wingtop Mini KVM Solution is the best choice for SOHO user, office where users need to manage 2 computers efficiently. It's designed for control of 2 computers using one keyboard, mouse, VGA monitor, speaker and microphone. With Mini KVM Solution, you can easily save the cost of multiple keyboards, monitors, mice, speakers and microphone, and also don't need to prepare extra cables between PC and console.

### Features

- Single console access 2 computers
- Computer selection via hotkeys.
- Hot-key selection: Scroll Lock /Caps Lock/Num Lock & Ctrl + Shift key
- Keyboard/mouse state saved and restored when switching ports
- LED indicators for easy status monitoring
- PnP configuration without any software or interface card
- Hot plug function to add or remove connected PCs for maintenance without powering down the KVM switch or PCs
- High resolution monitors supported up to 2048 x 1536, DDC 1/2B (depends on monitor & VGA card)
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice.
- OS Support: Windows 2000, Windows XP, Windows Vista, LINUX and FreeBSD



## WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.  
TEL: 886 2 2601 9881 ( 8686 ) FAX: 886 2 2601 3586(8229)  
<http://www.wingtop.com.tw> E-mail: [sales@wingtop.com.tw](mailto:sales@wingtop.com.tw)

- Auto Scan function to monitor computer operation.
- Non-powered.
- Dimensions is small and Weight is light.

## Specification

Model No		KVM-C102U	KVM-C102UA	KVM-C102P	KVM-C102PA
Function					
<b>Computer Connections</b>		2			
<b>Port Selection</b>		Hotkeys			
<b>Console Connectors</b>	Keyboard	1 x USB & 1 x Mini Dim6		1 x Mini Dim6	
	Mouse	1 x USB Type A		1 x Mini Dim6	
	Video	HDDDB-15 male			
	Audio	No	S+M	No	S+M
<b>KVM Connectors</b>	KVM data	2 x HDDDB-15 male			
<b>LEDs</b>		2(On Line/ Selection)			
<b>Emulation</b>		USB Keyboard & Mouse		PS/2 Keyboard & Mouse	
<b>Video</b>		2048 x 1536 DDC2B			
<b>Scan Interval</b>		5,10,15,20,25,30,35,40,60 Second			
<b>Power Consumption</b>					
<b>Environment</b>	Operating Temp.	0°~50°C			
	Storage Temp.	-20°~60°C			
	Humidity	0~80% RH, Non-condensing			
<b>Physical Properties</b>	Housing	Metal / Plastic			
	Weight	180g / 80g (without cable)			
	Dimensions	78 x 53.5 x 28 (mm)			
<b>Built-in Cable</b>		1.8M x 2			

\* The specification and pictures are subject to change without notice.

\* All trademarks and logos are the properties of their respective holders.



## WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.  
 TEL: 886 2 2601 9881 ( 8686 ) FAX: 886 2 2601 3586(8229)  
<http://www.wingtop.com.tw> E-mail: sales@wingtop.com.tw