



KVM-102PA/104PA (2/4-Port PS/2 KVM Switch)

The KVM (Keyboard, Video, Mouse) switch is a control unit that allows access to 2/4 computers from a single console (keyboard, monitor, mouse and Audio). With its custom designed connectors, the significantly reduces the number of ports required for a 2/4 port KVM switch. The design features a custom SPHD-15 male connector for the Keyboard, Video, Mouse and Audio, and SPHD-15 female connectors for that connect the switch to the computers.

Features

- Single console access 2/4 computers
- Computer selection via front panel pushbuttons and hotkeys.
- Hot-key selection: Scroll Lock /Caps Lock/Num Lock & Ctrl + Shift key
- Keyboard/mouse state saved and restored when switching ports
- LED indicators for easy status monitoring
- PnP configuration without any software or interface card
- Hot plug function to add or remove connected PCs for maintenance without powering down the KVM switch or PCs
- High resolution monitors supported up to 2048 x 1536, DDC 1/2B (depends on monitor & VGA card)
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice.
- OS Support: Windows 2000, Windows XP, Windows Vista, LINUX and FreeBSD
- Auto Scan function to monitor computer operation.
- Non-powered.



WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.
TEL: 886 2 2601 9881 (8686) FAX: 886 2 2601 3586(8229)
<http://www.wingtop.com.tw> E-mail:sales@wingtop.com.tw

Specification

Model No		KVM-102P	KVM-102PA	KVM-104P	KVM-104PA
Function					
Computer Connections		2		4	
Port Selection		Hotkey, Pushbutton			
Console Connectors	Keyboard	1 x Mini Dim6			
	Mouse	1 x Mini Dim6			
	Video	HDDDB-15 male			
	Audio	No	S+M	No	S+M
KVM Connectors	KVM data	2 x HDDDB-15 male		4 x HDDDB-15 male	
LEDs (On Line/ Selection)		2 x (Green/ Red)		4 x (Green/ Red)	
Emulation		PS/2 Keyboard & Mouse			
Video		2048 x 1536 DDC2B			
Scan Interval		5,10,15,20,25,30,35,40,60 Second			
Power Consumption					
Environment	Operating Temp.	0°~50°C			
	Storage Temp.	-20°~60°C			
	Humidity	0~80% RH, Non-condensing			
Physical Properties	Housing	Metal			
	Weight	280g (without cable)		420g (without cable)	
	Dimensions	130x 55 x 25 (mm)		200 x 55 x 25 (mm)	
Built-in Cable		2 x 1.8M		4 x 1.8M	

* The specification and pictures are subject to change without notice.

* All trademarks and logos are the properties of their respective holders.



WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.
 TEL: 886 2 2601 9881 (8686) FAX: 886 2 2601 3586(8229)
<http://www.wingtop.com.tw> E-mail:sales@wingtop.com.tw