



KVM-102UA/104UA (2/4-Port USB KVM Switch)

The KVM (Keyboard, Video, Mouse) switch is a control unit that allows access to 2/4 computers from a single console (keyboard, monitor, mouse and Audio). With its custom designed connectors, the significantly reduces the number of ports required for a 2/4 port KVM switch. The design features a custom SPHD-15 male connector for the Keyboard, Video, Mouse and Audio, and SPHD-15 female connectors for that connect the switch to the computers.

Features

- Single console access 2/4 computers
- Computer selection via front panel pushbuttons and hotkeys.
- Hot-key selection: Scroll Lock /Caps Lock/Num Lock & Ctrl + Shift key
- Keyboard/mouse state saved and restored when switching ports
- LED indicators for easy status monitoring
- PnP configuration without any software or interface card
- Hot plug function to add or remove connected PCs for maintenance without powering down the KVM switch or PCs
- High resolution monitors supported up to 2048 x 1536, DDC 1/2B (depends on monitor & VGA card)
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice.
- OS Support: Windows 2000, Windows XP, Windows Vista, LINUX and FreeBSD
- Auto Scan function to monitor computer operation.
- Non-powered.



WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.
TEL: 886 2 2601 9881 (8686) FAX: 886 2 2601 3586(8229)
<http://www.wingtop.com.tw> E-mail:sales@wingtop.com.tw

Specification

| Model No | | KVM-102U | KVM-102UA | KVM-104U | KVM-104UA |
|----------------------------------|-----------------|----------------------------------|-----------|-----------------------|-----------|
| Function | | | | | |
| Computer Connections | | 2 | | 4 | |
| Port Selection | | Hotkey, Pushbutton | | | |
| Console Connectors | Keyboard | 1 x USB & 1 x Mini Dim6 | | | |
| | Mouse | 1 x USB Type A | | | |
| | Video | HDDB-15 male | | | |
| | Audio | No | S+M | No | S+M |
| KVM Connectors | KVM data | 2 x HDDB-15 male | | 4 x HDDB-15 male | |
| LEDs (On Line/ Selection) | | 2 x (Green/ Red) | | 4 x (Green/ Red) | |
| Emulation | | USB Keyboard & Mouse | | | |
| Video | | 2048 x 1536 DDC2B | | | |
| Scan Interval | | 5,10,15,20,25,30,35,40,60 Second | | | |
| Power Consumption | | | | | |
| Environment | Operating Temp. | 0°~50°C | | | |
| | Storage Temp. | -20°~60°C | | | |
| | Humidity | 0~80% RH, Non-condensing | | | |
| Physical Properties | Housing | Metal | | | |
| | Weight | 280 g (without cable) | | 420 g (without cable) | |
| | Dimensions | 130x 55 x 25 (mm) | | 200 x 55 x 25 (mm) | |
| Built-in Cable | | 2 x 1.8M | | 4 x 1.8M | |

* The specification and pictures are subject to change without notice.

* All trademarks and logos are the properties of their respective holders.



WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.
 TEL: 886 2 2601 9881 (8686) FAX: 886 2 2601 3586(8229)
<http://www.wingtop.com.tw> E-mail:sales@wingtop.com.tw