

## Specification

- **Designed for mountable industrial Panel PC**
  - **Aluminum made front panel meet NEMA4/IP65 (optional)**
  - **Processor:** Socket 478 for Intel® Pentium® 4 or celeron (FSB 400 MHz).
  - **15.0" TFT LCD Display:**
    - Resolutions 1024x768 (XGA)
    - Backlight MTBF: 50000 hours
    - Contrast ratio: 350:1
    - Brightness: 250 cd/m<sup>2</sup>
    - 500/1600 cd/m<sup>2</sup> brightness sunlight read-able (optional)
  - **System Memory:**
    - 3x168-pin DIMM sockets
    - Max capacity: Up to 3 GB
  - **Expansion slot**
    - Eight slot Backplane with one PICMG CPU card.
    - 4 x PCI & 4 x ISA expansion slot (Total only 7 expansion slot can be use)
  - **Driver Bay:**
    - 2 x 3.5" Remove-able driver bay
    - 1 x 5.25 Slim size CD-ROM
    - 1 x 3.5" FDD
  - **VGA:** SMI 712 controller
  - **Ethernet:** 10/100bps fast Ethernet controller
  - **SSD:** Support Disk On Chip 2000 series up to 288 MB
  - **Watchdog timer:** 1~127 sec
- 
- **I/O:**
    - 2 x Serial. (1 x RS-232, 1 x RS-232/422/485)
    - 1 x Parallel
    - 4 x USB
    - 1 x RJ-45 LAN Jack
    - PS/2 Keyboard/mouse connector
    - 1 x IrDA header
  - **Power Supply**
    - DC Output rating: 250 W (300/350 W optional)
    - Input voltage: 100~127/200~240VAC @ 47/63 Hz
    - MTBF: 80,000 hrs.
    - Safety: UL/ cUL/ TÜV/ FCC/ CE approved (PFC Optional)
  - **Chassis Colors:** Black, OEM color welcome
  - **Environment Specification**
    - Operating Temperature: 0° ~ 50° C (32 ~ 113° F)
    - Relative Humidity: 5~85%
  - **OEM Specification Welcome**
  - **Option**
    - Resistive touch screen (RS-232 / USB)
  - **Dimensions**
    - W.430mm x H.285mm x D.175mm
    - N.W. 8.5 KGS, G.W. 10 KGS, CUFT. 2.7



## WINGTOP CO.,LTD.

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.

TEL: 886 2 2601 9881 ( 8686 )

FAX: 886 2 2601 3586 (8229)

<http://www.wingtop.com.tw>

E-mail:sales@wingtop.com.tw

May/29/2003