

## INDUSTRIAL 15" TFT LCD Panel PC

**Specification**

- **Designed for mountable industrial Panel PC**
- **Aluminum made front panel meet NEMA4/IP65 (optional)**
- **Processor:** Socket 478 for Intel® Pentium® 4 (FSB 400/533 MHz) supports Hyper Threading Technology (3.0)
- **15.0" TFT LCD Display:**
  - Resolutions 1024x768 (XGA)
  - Backlight MTBF: 50000 hours
  - Contrast ratio: 350:1
  - Brightness: 250 cd/m<sup>2</sup>
  - 500/1600 cd/m<sup>2</sup> brightness sunlight read-able (optional)
- **System Memory:**
  - 2 x DDR socket
  - Max capacity: Up to 2 GB
- **Expansion slot**
  - 3 x PCI slot
- **Driver Bay:**
  - 2 x 3.5" Remove-able driver bay
  - 1 x 5.25 Slim size CD-ROM
  - 1 x 3.5" FDD
- **Audio:** AC' 97 link controller
- **Ethernet:** 10/100bps fast Ethernet controller
- **I/O:**
  - 2 x Serial
  - 1 x Parallel
  - 2 x USB
  - 1 x RJ-45 LAN Jack
  - PS/2 Keyboard/mouse connector
  - 1 x Audio/game port
- **Power Supply**
  - DC Output rating: 250 W (300/350W optional)
  - Input voltage: 100~127/200~240VAC @ 47/63 Hz
  - MTBF: 80,000 hrs.
  - Safety: UL/ cUL/ TÜV/ FCC/ CE approved (PFC Optional)
- **Chassis Colors:** Black, OEM color welcome
- **Environment Specification**
  - Operating Temperature: 0° ~ 50°C (32 ~ 113° F)
  - Relative Humidity: 5~85%
- **OEM Specification Welcome**
- **Option**
  - Resistive touch screen (RS-232 / USB)
- **Dimensions**
  - W.430mm x H.285mm x D.175mm
  - N.W. 8.5 KGS, G.W. 10 KGS, CUFT. 2.7

**WINGTOP CO.,LTD.**

No. 9, Kong 6Th Rd., 2nd Industry Park, Lin Kou, Taipei Hsien, Taiwan, R. O. C.

TEL: 886 2 2601 9881 ( 8686 )

FAX: 886 2 2601 3586 (8229)

<http://www.wingtop.com.tw>

E-mail:sales@wingtop.com.tw

May/29/2003